

SMP QUICK COUPLER

TWO WAY QUICK COUPLERS

With SMP's Two Way Quick Couplers you can quickly and easily change tools between different tasks, depending on the type of work being carried out. Thanks to the quick coupler's design, the operator can easily chose to work for example with a reverse digging angle. SMP Two Way Quick Coupler is suitable for excavators from 0,5 tonnes to 40 tonnes and is constructed according to the Nordic Standard.



TECHNICAL SPECIFICATIONS TURNABLE QUICK COUPLERS SMP

Basic dimensions for Nordic standard

Model	Width	Pin distance (mm)	Pin dia (mm)
S30/180	180	c/c 230	Ø30
S40	200	c/c 300	Ø40
S45	290	c/c 430	Ø45
S50	270	c/c 430	Ø50
S60	340	c/c 480	Ø60
S70	450	c/c 600	Ø70
S80	590	c/c 670	Ø80

Model	Locking	Machine size (tonne)	Approx weight kg
S30/180	Semi automatic	0.5 - 2	15
S30/180	Hydraulic	0.5 - 2	15
S40	Semi automatic	2 - 5	30
S40	Mechanical	2 - 5	30
S40	Hydraulic	2 - 5	30
S45	Mechanical	5 - 12	75
S45	Hydraulic	5 - 12	75
S50	Mechanical	5 - 13	75
S50	Hydraulic	5 - 15	75
S60	Hydraulic	12 - 18	160
S70	Hydraulic	17 - 25	280
S80	Hydraulic	25 - 40	320

Weights can vary depending on design of product